

## PURECELL SYSTEM BENEFITS

### Energy Security

Proven PAFC fuel cell technology that is setting durability records

### Energy Productivity

Increased efficiency and continuous on-site generation reduces energy costs

### Energy Responsibility

No emissions equals sustainability

## PURECELL SYSTEM COMPETITIVE ADVANTAGES

### Long Life

Industry leading 10-year cell stack life assures high availability and low service cost

### Modular & Scalable

Solutions for multi-megawatt applications to meet growing energy demand

### Experience

60+ years of fuel cell development

### High Efficiency

Up to 90% total CHP Efficiency

### Small Footprint

Highest power density among clean generation technologies

### Flexible Siting

Indoor, outdoor, rooftop, multi-unit

## RATED POWER OUTPUT: 440KW, 480VAC, 60HZ

Characteristic	Units	Value <sup>1</sup>
Electric Power Output	kW/kVA	440/517
Electrical Efficiency	%, LHV	50
Peak Overall Efficiency	%, LHV	90
Hydrogen Purity, Minimum <sup>2</sup>	%	99.9
Hydrogen Input	Energy kW (MMBtu/h), HHV	1,039 (3.59)
	Volume <sup>3</sup> Nm <sup>3</sup> /h (SCFH)	295 (10,328)
	Mass kg/h (lbs/h)	26.4 (58.1)
Heat Output @ up to 121°C (250°F)	kW (MMBtu/h)	352 (1.20)

## FUEL

Supply..... Hydrogen Gas  
Inlet Pressure<sup>4</sup> ..... 5 ± 0.25 bar(g)

## EMISSIONS

Zero emissions of CO<sub>2</sub>, NO<sub>x</sub>, SO<sub>x</sub>, CO, and VOCs. Heat output can offset additional CO<sub>2</sub> from combustion heat generation (e.g., boilers).

## OTHER

Ambient Operating Temp ..... Max Power -20°F to 104°F (-29°C to 40°C)<sup>5</sup>  
Sound Level ..... < 65 dBA @ 33 ft. (10m)  
Water Consumption ..... None



**Daesan Green Energy Project**  
50 MW | 114 Units | South Korea

## NOTES

1. Average performance during 1<sup>st</sup> year of operation. Refer to the Product Data and Applications Guide for performance over the operating life of the powerplant.
2. Contact HyAxiom for requirements on other gas constituents or for lower purity H<sub>2</sub>.
3. Based on Hydrogen gas higher heating value of 343 Btu / SCF (12.8 MJ/Nm<sup>3</sup>).
4. Contact HyAxiom for lower inlet pressures.
5. Derate at ambient temperatures outside of specified range. Contact HyAxiom for details.

HyAxiom, Inc.  
Corporate Headquarters  
101 East River Drive  
East Hartford, CT 06108  
860.727.2253  
www.hyaxiom.com

